Printer		SELPHY CP910
PRINTING SYSTEM		
	Method	Dye-sublimation thermal transfer printing system
	Maximum Resolution	300 x 300 dpi
	Colours	3 colour inks with protective over coating, 256 levels per colour (24 bit colour depth)
MEDIA & CARTRIDGE		
	Postcard Size	148 x 100 mm - [KP-36IP, KP-72IN, KP-108IN]
	Credit Card Size	86 x 54 mm - [KC-36IP] [1]
	Credit Card Size Stickers	86 x 54 mm - [KC-18IF] [1]
	Square Stickers	50 x 50 mm - [KC-18IS] [1]
	Mini Stickers	22.0 x 17.3 mm (x8 stickers on one sheet) - [KC-18IL] [1]
	Ink Cartridge	Included with media
	Image Longevity	100 Years Print [2]
MEDIA INPUT		
	Sheet Feeder	Auto feed from paper cassette
PRINT SPEEDS		
	Postcard Size	approx. 47 sec [3]
	Credit Card Size	approx. 27 sec [3]
	Credit Card Size Stickers	approx. 27 sec [3]
	Mini Stickers	approx. 27 sec [3]
PRINTING		
	Print Modes	Easy print (Selection of individual images and number of copies for batch printing), All image print (Selection of all images and number of copies for batch printing), DPOF Image Print, ID Photo Print (Multi-size, Standard, Custom size), Cropping
	Print Settings	Date, Red-eye correction, Print finish (Glossy, Semi-Gloss (Pattern 1/ Pattern 2)), Bordered, Borderless, Layout (1-up, 2-up, 4-up, 8-up, Index [4], Shuffle), Smooth Skin, My Colors (Off, Vivid, Neutral, Positive Film, Sepia, Black & White), Image optimize, Manual brightness adjustment, Power saving, Exif
PRINT METHOD		
	Direct Printing From a Camera	PictBridge compliant (USB and Wireless LAN)
	Direct From a Memory Card	Supported card types: SD, SDHC, SDXC USB Flash Memory [6] Supported via Adapter [5]: miniSD, miniSDHC, microSD, microSDHC, microSDXC
	Direct From a Camera Phone	Compatitble with smartphones, tablets and portable devices via Wi-Fi (Direct or Infrastructure connection): iOS devices - using Canon Easy-PhotoPrint app & Apple AirPrint Android devices - using Canon Easy-PhotoPrint app
	Print From a Computer	Yes, requires standard USB cable or compatible Wi-Fi connection.
INTERFACE		
	Camera	USB type A port on printer, Wi-Fi (PictBridge via WLAN - DPS over IP compatible)
	Computer	USB mini-B port on printer, Wi-Fi (IEEE802.11 b/g)
	LCD Monitor	6.8 cm (2.7") Colour TFT viewer with multi-language user interface and tilt mechanism (Languages: English, German, French, Italian, Spanish, Russian, Simplified Chinese, Korean, Thai, Hindi, Vietnamese, Malaysian, Japanese, Portuguese)

SUPPORTED OPERATING SYSTEM		
	PC	USB connection: Windows 8.1 / 8 / 7 SP1 Wi-Fi connection: Windows 8.1 / 8 / 7 SP1
	Macintosh	USB connection: Mac OS X 10.6.8 - 10.9 Wi-Fi connection: Mac OS X 10.6.8 - 10.9
SOFTWARE		
	Browsing & Printing	SELPHY Photo Print
	Drivers	Windows / Mac
POWER SOURCE		
	AC Power Supply	Yes, supplied
	Battery Pack	Yes, optional NB-CP2L (Approx. 36 Postcard size prints per full charge. Requires Charge Adapter CG-CP200) [5]
	Power Consumption	Approx. 4W (standby), approx. 60W (printing)
ACCESSORIES		
	Case	CP Printer Carrying Case DCC-CP3 CP Printer Carrying Case DCC-CP2
	Paper Cassette	Postcard Size paper cassette [PCP-CP400] Card Size paper cassette [PCC-CP400] Dust Protection Cover DPC-CP100
	Power Supply & Battery Chargers	AC Adapter CA-CP200B, Charge Adapter CG-CP200 (for Battery Pack NB-CP2L)
PHYSICAL SPECIFICATIONS		
	Operating Environment	5 – 40 °C, 20 – 80% humidity
	Dimensions	178.0 x 127.0 x 60.5 mm (printer only without protrusions)
	Weight	810g (Excluding Ink Cartridge and Paper Cassette)

All data is based on Canon's standard testing methods.
Subject to change without notice.

[1] Requires optional paper cassette
[2] To test the image permanence of prints that are stored in an album, we use an accelerated testing method similar to how the
[3] Print speed can vary dependent on data size, print method, memory card and capacity and is measured from start of printing
[4] Modes/features available may differ dependent on camera model or use of memory card to print
[5] Requires adapter (sold separately)
[6] Irregularly sized images, or images that have been edited on a computer may not display or print. USB Devices that are not identified as "Removable media" (such as external hard drives) or do not use the FAT or exFAT file system or have GUID partition tables created on a Macintosh computer are not supported.